

Число жил и номинальное сечение, мм ²	Наружный диаметр кабеля, мм		Масса 1 км кабеля, кг	
	660 В	1000 В	660 В	1000 В
Кабели марки АВВГ с круглыми жилами				
1 x 2.5	5.4	5.8	35	40
1 x 4	6.1	6.7	46	54
1 x 6	6.5	7.1	55	63
1 x 10	7.7	7.9	78	81
1 x 16	9.3	9.5	114	118
1 x 25	10.8	11.0	161	165
1 x 35	11.8	12.0	197	203
1 x 50	13.5	13.7	263	270
1 x 70		15.2		345
1 x 95		17.3		448
1 x 120		19.2		554
1 x 150		22.2		684
1 x 185		24.8		858
1 x 240		27.7		1072
1 x 300		30.8		1329
2 x 2.5	8.4	9.8	64	87
2 x 4	10.3	11.5	99	117
2 x 6	11.3	12.5	118	137
2 x 10	13.6	14.0	167	174
2 x 16	15.5	15.9	220	228
2 x 25	19.0	19.4	331	340
2 x 35	21.0	21.4	407	417
2 x 50	24.8	25.2	565	578
2 x 70		28.2		735
2 x 95		32.4		952
2 x 120		35.8		1170
2 x 150		41.8		1443
2 x 185		46.7		1800
3 x 2.5	9.4	10.3	92	105
3 x 4	10.9	12.2	122	145
3 x 6	11.9	13.2	148	173

3 x 10	14.4	14.8	215	225
3 x 16	16.4	16.9	289	300
3 x 25	20.2	20.6	438	452
3 x 35	22.3	22.8	546	561
3 x 50	26.4	26.8	763	782
3 x 2.5 + 1 x 2.5	10.2	11.2	109	127
3 x 4 + 1 x 2.5	11.8	12.8	141	165
3 x 6 + 1 x 2.5	12.6	13.9	167	194
3 x 6 + 1 x 4	13.0	14.4	175	206
3 x 10 + 1 x 4	14.8	15.7	239	255
3 x 10 + 1 x 6	15.2	16.3	247	266
3 x 16 + 1 x 6	16.9	17.9	319	340
3 x 16 + 1 x 10	18.5	18.9	360	373
3 x 25 + 1 x 10	20.8	21.3	486	502
3 x 25 + 1 x 16	21.5	21.9	511	527
3 x 35 + 1 x 16	24.2	24.6	642	659
3 x 50 + 1 x 16	27.2	27.7	833	854
3 x 50 + 1 x 25	28.1	28.5	876	899
3 x 70 + 1 x 25		31.0		1117
3 x 95 + 1 x 35		36.1		1491
3 x 120 + 1 x 35		39.4		1763
3 x 150 + 1 x 50		46.6		2249
3 x 185 + 1 x 50		51.5		2710
4 x 2.5	10.2	11.2	109	127
4 x 4	11.8	13.3	148	177
4 x 6	13.0	14.4	181	213
4 x 10	15.8	16.3	267	279
4 x 16	18.5	18.9	379	394
4 x 25	22.3	22.7	553	570
4 x 35	25.0	25.5	716	735
4 x 50	29.1	29.6	971	995
Кабели марки АВВГ с секторными жилами				
3 x 50		29.6		850
3 x 70		32.4		1075
3 x 95		36.0		1408

3 x 120		38.5		1672
3 x 150		41.1		1982
3 x 185		44.1		2373
3 x 240		49.1		3075
3 x 50 + 1 x 25		29.0		931
3 x 70 + 1 x 35		32.2		1190
3 x 95 + 1 x 50		36.5		1585
3 x 120 + 1 x 70		39.5		1922
3 x 150 + 1 x 70		42.5		2235
3 x 185 + 1 x 95		46.5		2764
3 x 240 + 1 x 120		52.1		3516
4 x 50		29.8		1036
4 x 70		33.0		1331
4 x 95		37.5		1763
4 x 120		40.5		2116
4 x 150		43.7		2526
4 x 185		47.7		3085
4 x 240		53.5		3965

Информация может изменяться в зависимости от производителя.