

Число жил и номинальное сечение, мм ²	Наружный диаметр кабеля, мм		Масса 1 км кабеля, кг	
	660 В	1000 В	660 В	1000 В
Кабели марки ВБбШвнг-LS с круглыми жилами				
2 x 4	14.3		415	
2 x 6	15.3	16.5	489	549
2 x 10	17.7	18.1	674	688
2 x 16	20.7	21.1	926	952
2 x 25	23.0	23.4	1216	1244
2 x 35	25.6	26.0	1540	1571
2 x 50	28.6	29.0	1954	1988
3 x 4	14.8		467	
3 x 6	15.9	17.2	560	625
3 x 10	18.5	18.9	779	802
3 x 16	21.8	22.2	1098	1127
3 x 25	24.6	25.0	1501	1533
3 x 35	27.0	27.4	1886	1920
3 x 50	30.2	30.6	2414	2452
3 x 4 + 1 x 2.5	15.8		526	
3 x 6 + 1 x 2.5	16.5	17.9	606	669
3 x 6 + 1 x 4	17.0	18.4	638	706
3 x 10 + 1 x 4	18.9	19.8	822	873
3 x 10 + 1 x 6	19.4	20.4	861	921
3 x 16 + 1 x 6	22.3	22.8	1161	1190
3 x 16 + 1 x 10	22.9	23.3	1227	1258
3 x 25 + 1 x 10	25.2	25.7	1598	1631
3 x 25 + 1 x 16	26.7	27.2	1750	1787
3 x 35 + 1 x 16	28.4	28.9	2087	2125
3 x 50 + 1 x 16	31.0	31.5	2563	2602
3 x 50 + 1 x 25	31.9	32.3	2710	2752
4 x 4	15.8		537	
4 x 6	17.0	18.4	652	719
4 x 10	19.9	20.4	921	950
4 x 16	23.6	24.4	1315	1375
4 x 25	26.7	27.2	1819	1856

4 x 35	29.3	29.8	2301	2342
4 x 50	32.9	33.4	2464	3009
Кабели марки ВБШвнг-LS с секторными жилами				
3 x 50		30.7		2280
3 x 70		33.7		2961
3 x 95		37.6		3853
3 x 120		40.2		4633
3 x 150		43.2		5658
3 x 185		47.3		6906
3 x 240		52.4		8584
3 x 50 + 1 x 25		32.9		2594
3 x 70 + 1 x 35		36.3		3395
3 x 95 + 1 x 50		40.2		4395
3 x 120 + 1 x 70		43.1		5388
3 x 150 + 1 x 70		46.6		6363
3 x 185 + 1 x 95		50.4		7768
3 x 240 + 1 x 120		56.2		9897
4 x 50		33.7		2853
4 x 70		37.3		3765
4 x 95		41.2		4893
4 x 120		44.1		5922
4 x 150		47.8		7180
4 x 185		51.6		8675
4 x 240		57.6		11145

Информация может изменяться в зависимости от производителя.