

Число жил и номинальное сечение, мм <sup>2</sup>	Наружный диаметр кабеля, мм		Масса 1 км кабеля, кг	
	660 В	1000 В	660 В	1000 В
<b>Кабели марки ВВГнг-LS с круглыми жилами</b>				
2 x 1.5	7.6	8.4	97	113
2 x 2.5	8.3	9.7	126	158
2 x 4	10.3	11.5	194	227
2 x 6	11.3	12.5	249	285
2 x 10	13.7	14.1	386	400
2 x 16	16.7	17.1	588	606
2 x 25	20.4	20.8	951	975
2 x 35	22.4	22.8	1211	1237
2 x 50	26.4	26.8	1666	1697
3 x 1.5	8.0	9.5	115	148
3 x 2.5	9.4	10.3	167	188
3 x 4	10.8	12.1	236	273
3 x 6	11.9	13.2	308	348
3 x 10	14.5	14.9	484	499
3 x 16	17.8	18.6	741	781
3 x 25	21.6	22.0	1185	1211
3 x 35	24.2	24.6	1551	1581
3 x 50	28.0	28.4	2093	2128
3 x 1.5 + 1 x 1	9.3	10.2	149	172
3 x 1.5 + 1 x 1.5	9.3	10.2	153	175
3 x 2.5 + 1 x 1.5	10.2	11.1	194	219
3 x 4 + 1 x 2.5	11.8	12.8	277	306
3 x 6 + 1 x 2.5	12.5	13.9	341	385
3 x 6 + 1 x 4	13.0	14.4	365	413
3 x 10 + 1 x 4	14.9	15.8	519	553
3 x 10 + 1 x 6	15.4	16.4	550	590
3 x 16 + 1 x 6	18.7	19.2	813	834
3 x 16 + 1 x 10	19.3	19.7	869	892
3 x 25 + 1 x 10	22.2	22.7	1267	1293
3 x 25 + 1 x 16	24.1	24.6	1429	1461
3 x 35 + 1 x 16	25.6	26.1	1729	1761

3 x 50 + 1 x 16	28.8	29.3	2224	2258
3 x 50 + 1 x 25	29.7	30.1	2365	2402
4 x 1.5	9.3	10.2	153	175
4 x 2.5	10.2	11.1	201	226
4 x 4	11.8	13.2	287	331
4 x 6	13.0	14.4	379	427
4 x 10	15.9	16.4	600	619
4 x 16	20.0	20.4	945	970
4 x 25	24.1	24.6	1494	1526
4 x 35	26.5	27.0	1930	1965
4 x 50	30.7	31.2	2606	2646
<b>Кабели марки ВВГнг-LS с секторными жилами</b>				
3 x 50		28.5		1972
3 x 70		31.5		2610
3 x 95		35.4		3471
3 x 120		38.0		4216
3 x 150		41.0		5104
3 x 185		45.1		6253
3 x 240		50.2		8027
3 x 50 + 1 x 25		30.7		2262
3 x 70 + 1 x 35		33.7		2990
3 x 95 + 1 x 50		38.0		3985
3 x 120 + 1 x 70		40.9		4939
3 x 150 + 1 x 70		44.0		5827
3 x 185 + 1 x 95		48.2		7234
3 x 240 + 1 x 120		53.6		9239
4 x 50	31.3	31.5	2483	2512
4 x 70		35.1		3386
4 x 95		39.0		4472
4 x 120		41.9		5460
4 x 150		45.6		6675
4 x 185		49.4		8126
4 x 240		55.4		10526

*Информация может изменяться в зависимости от производителя.*